# MicroCoMPASS™

Micro Compact Multi-purpose Advanced Stabilized System - Maritime



### General

The MicroCoMPASS payload is the latest member of the battleproven CoMPASS stabilized EO payload family, in use worldwide.

#### Features:

- Ultra-lightweight, extremely compact design, optimized for installation on small maritime platforms
- Cutting-edge electro-optical technology, delivering superb day and night observation & surveillance capabilities, even in harsh weather conditions
- Single LRU integrating four EO elements, large format continuous zoom thermal imager, zoom color TV camera with low light mode, target illuminator and eye-safe laser range finder (ELRF)
- High stabilization level in a harsh sea state
- Meets even the most severe environmental requirements



# MicroCoMPASS

### Micro Compact Multi-purpose Advanced Stabilized System - Maritime

### **Applications**

- · Coastal patrol
- · Riverine operations
- Special forces
- Surveillance
- · Search & Rescue

### Main Advantages & Features

- · Stabilized real-time video
- · Long range continuous zoom thermal imager and zoom color CCD camera
- · Automatic tracking of observed targets
- Lightweight, compact design with low power consumption
- · Simple and straightforward installation
- Interface with platforms, fire control and navigation systems
- · High reliability



_		
100	b b l c b l	1 1 1 2 + 2
		1 1414
		l Data

System

8.2" · Diameter · Weight <9 Kg

Angular coverage

- Azimuth N x 360° - Elevation +30° to -85° · Environmental conditions MIL-STD-810 · Video output standard PAL, NTSC

Thermal Channel

 FLIR Cooled 3rd generation 3-5µm FPA detector

640 x 512

FOV (continuous zoom)

- Narrow 2.5° x 2° - Wide

- Electronic zoom

17.5° x 14°

Day Channel

 Color TV camera 1/4" CCD detector

FOV (continuous zoom)

- Narrow 1.7° X 1.2° - Wide 42° x 32° - Electronic zoom X12

Laser

Laser target illuminator

830 nm (NVG compatible)

Eye-safe laser range finder (ELRF)

- Laser wavelength 1.54µm

- Repetition rate 20 ppm continuously

Laser designator (optional)

External Interface

RS 232/422, ETHERNET



Elbit Systems Ltd.

E-mail: istar@elbitsystems.com

www.elbitsystems.com





