TIFCS

Thermal Imaging Fire Control System - Gunner Sight



TIFCS is an advanced, compact, robust, modular, user-friendly gunner sight. A long-range system, it is optimal for both day and night, stationary and on the move operation, and is designed for rapid and high-accuracy target engagement, in all combat scenarios.

Main Advantages & Features

- Unique and modular configuration add-on system
- Dual-axis stabilized sight
- Advanced 8-12µm thermal channel
- High resolution TV channel (DVO optional)
- Eyesafe long-range laser rangefinder
- Based on mature technology; passed field tests, including firing
- and environmental conditions
- · Integrated electronic control unit
- Compact interface to platform, designed to fit small turrets

Applications

- Main battle tanks
- · Armoured fighting vehicles
- Tactical vehicles



TIFCS

Thermal Imaging Fire Control System - Gunner Sight



Technical Data

Si	q	h	t
	_		

Line of sight (LOS)

- Elevation -10° to +22° - Azimuth ±3°

LOS stabilization acccuracy

- Elevation 0.1 mRad - Azimuth 0.1 mRad - Sight-to-gun accuracy 0.2 mils

Thermal Imager

Spectral region Detector type Fields of view (FOV)

- Wide

- Narrow

8-12µm

TDI MCT, 288 x 4 elements

10.3° x 6° (± 10%) 3° x 2° (± 10%)

ELRF

Laser wavelength 1535 nm (class 1) repetition rate 1 pps Target discrimination 50 meters Max. target range 9000 m Range accuracy ± 5 m Laser safety Eyesafe Class 1

TV Channel (DVO Optional)

Sensor type Spectral band Resolution Video format Fields of view (FOV)

- Wide - Narrow

Focus

CCD

650-850 nm, monochrome 1360 x 1024

SMPTE 292

20°

4.5°

200 - INF [meter] without adjusting focus

Range Performance*

Thermal Channel





- Identification
- Recognition
- Detection (WFOV)
- Detection (NFOV)



Recognition

Detection (WFOV)

Detection (NFOV)



Elbit Systems Ltd.

Advanced Technology Center, P.O.B 539, Haifa 3100401, Israel E-mail: istar@elbitsystems.com www.elbitsystems.com







^{*} Range performances are defined at the indicated FOV and can be improved to meet the requirements by E-zoom NFOV (2°)