

DCoMPASS™

Digital Compact Multi-Purpose Advanced Stabilized System - UAV



General

The DCoMPASS payload is the one of the newest members of our CoMPASS battle-proven stabilized EO payload family, in service with leading customers worldwide.

- Delivers superb day and night intelligence, surveillance, target acquisition and tactical reconnaissance (ISTAR) capabilities in the harshest weather conditions
- Single LRU configuration integrating up to five EO elements: HD color TV camera with optional low light mode, large format thermal imager, laser target illuminator, eyesafe laser rangefinder (ELRF) and laser target designator
- Lightweight, small size payload made possible by new miniature digital electronics and advanced lightweight materials
- Precise geo-location and pointing capabilities provided by incorporated gimbal IMU (Inertial Measurement Unit)
- Battle proven, military qualified for airborne application

DCoMPASS

Digital Compact Multi-Purpose Advanced Stabilized System - UAV

Applications


- Border and maritime patrol
- Surveillance
- Law enforcement
- Laser targeting

Main Advantages & Features

- Highly stabilized crystal clear image on both HD color TV and thermal imager
- Compact and lightweight design permits additional payload and fuel capacity in the carrying platform while facilitating future upgrades
- Inertial Measurement Unit (IMU) provides highly accurate geo-location and rock solid stabilization
- Unique in-flight boresight mechanism enables long range precise laser designation
- Simple system integration with helmet mounted systems (HMS), radar and fire control applications
- Advanced video enhancement package including: haze penetration, color restoration and sharpening features
- Step & Stare feature provides ISR persistence

Technical Data

System	
• Diameter	15"
• Weight	<33 Kg
• Angular coverage	
• - Azimuth	N x 360°
• - Elevation	+35° to -85°
• Environmental conditions	MIL-STD-810F
Day Channel (HD)	
• Camera type	Large format digital CCD color camera
• Sensor	2/3" CCD
• No. of pixels	1394 x 1040
• FOV (continuous zoom)	
• - Narrow	0.59° x 0.44°
• - Wide	21.25° x 16°
• Thermal Imager	
• FLIR	Cooled 3rd generation 3-5 µm FPA with 640 x 512 pixels



- FOV

	FLIR A - TOPAZ	FLIR B - LOTUS
Wide	24° X 18°	13.7° X 10.4°
Medium	Continuous	2.0° x 1.5°
Narrow	0.8° X 0.6°	0.61° x 0.46°

Laser Sensors

- Laser Rangefinder (Eyesafe)
 - Wavelength 1.54 µm
 - Rate 1 pps
- Dual Wavelength Laser Target Designator & Rangefinder (LRFTD)
 - Transmitter Diode-pumped advanced technology
 - Wavelength 1.064 µm / 1.57 µm
 - Max pulse rate 20pps
- Laser target illuminator/pointer
 - Wavelength 830 nm (NVG compatible)

Interface Communications

- RS422
- MIL-STD-1553
- Ethernet

Video Output

- PAL, NTSC
- Gigabit Ethernet (GigE)

Additional features

- Geo-location using Inertial Measurements Unit (IMU)
- Auto-tracker
- Step & Stare
- Picture In Picture (PIP)



Elbit Systems Ltd.

E-mail: istar@elbitsystems.com www.elbitsystems.com

Follow us on   